RCF™ Structural Epoxy Injection Resin | Revision Date 7/25/2019

1633 Thornwood Dr. Heath, OH 43056 USA P: +1 888 684 3889

01: PRODUCT & COMPANY IDENTIFICATION

RHINO PRODUCTS USA, INC. 1633 THORNWOOD DRIVE HEATH, OH 43056

Product Name: RCF™ Structural Epoxy Injection Resin

Common Name: Polyamine

Product Code: RCF-IREP

Synonyms: Amines Liquid Corrosive Product Use: Epoxy Injection Resin

Emergency Phone: CHEMTREC 1 800 424 9300

02: HAZARDS IDENTIFICATION

GH Glassification

HEALTH HAZARD CATEGORY Skin Corrosion 1В Serious Eye Damage Skin Sensitization

Hazard Statement

H314: Causes severe skin burns and eye damage H317: May cause an allergic skin reaction

Precautionary Statement

Inhalation:

Harmful if inhaled and may cause delayed lung injury. Can cause severe respiratory tract burns. Risk of serious damage to the lungs. May cause nose, throat

and lung irritation. Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory system.

Causes skin burns. Skin Contact:

Causes eye burns. May cause blindness. Severe eye irritation. Eve Contact:

If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach. Ingestion:

Prolonged exposure Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause. Sore throat, Eye disease, Skin Disorders and Allergies.

03: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Cas#	Chemical Name	%	OSHA PEL	ACGUH TLV
Component A				
25085-99-8	Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	>60%	NE	NA
68609-97-2	Aliphatic Glycidyl Ether	<40%	NE	NE
CE330 Part B				
84852-15-3	Nonylphenol	>40%	NE	NE
140-31-8	Aminoethylpiperazine	<10%	NE	NE
9046-10-0	Polyoxypropylenediamine	<30%	NE	NE
90-72-2	2,4,6 Tri (dimethylaminomethyl)phenol	<10%	10 mg/m3	5 mg/m3
112-24-3	Triethylenetetramine	<10%	NE	NE

None of the remaining components are considered a hazardous material or carcinogen (1910.1200 Hazard Communication (d) 4.)

NE= Not Established NA=Not Applicable

04: FIRST AID MEASURES

General Advice: Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped

trained personnel should begin cardiopulmonary resuscitation immediately

Inhalation: If respiratory irritation occurs, go to fresh air, flood work area with fresh air. If irritation continues seek medical attention.

Skin Contact: Remove contaminated clothing and shoes. Wash affected area(s) throughly with soap and water. If irritation persists, seek medical attention.

SOLVENTS SHOULD NOT BE USED because they carry the irritant into the skin.

Flush the eyes with plenty of water for at least 15 minutes. If necessary, gently hold eyelids open during the flush. Immediately seek medical attention. Eye Contact: Ingestion:

Obtain immediate medical attention. Do not induce vomiting. Should vomiting occur, be sure to keep victim's head below hips to avoid

aspiration of vomit into the lungs

05: FIRE FIGHTING MEASURES

Special Fire Fighting Prodedures: none. Avoid breathing smoke. NFPA Class B-C extinguisher (dry chemical or foam) for class 1C fires. Water spray may be ineffective on fire but can protect fire-fighters and cool closed containers. Use fog nozzels if water is used. Use supplied breathing masks.

Protection of firefighters: Fire may produce irritating, corrosive and/or toxic gases. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots and in enclosed spaces SCBA. Structural firefighters protective clothing will only provide limited protection



1-888-684-3889 | www.RhinoCarbonFiber.com

© All Rights Reserved

SAFETY DATA SHEET

RCF™ Structural Epoxy Injection Resin | Revision Date 7/25/2019

1633 Thornwood Dr. Heath, OH 43056 USA P: +1 888 684 3889

02

06: ACCIDENTAL RELEASE MEASURES

Keep people away from and upwind of spill/leak. Avoid inhalation of vapors and spray mists. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Follow facility/company's emergency plans. Personal Precautions:

Small Spills: Absorb with an inert material (sand, vermiculite). Sweep or scoop up and put into disposal containers. Flush area immediately with water (prevent water

Dike area far ahead of liquid spill for later disposal. Do not release into sewers or waterways. Absorb with an inert material (sand, vermiculite). Sweep or scoop up into disposal containers. Flush area immediately with water (prevent water from entering waterways) Large Spills:

Follow applicable OSH regulations (29 CFR 1910.120). Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area or until spill clean-up has been completed. Regulatory Requirements:

07: HANDLING AND STORAGE

Handling Precautions: For professional use only. Avoid eye/skin contact. Wash after using and before eating or smoking. Avoid breathing vapors. Use as directed. Avoid

uncontrolled mixing with other mixtures (stong acids,bases and oxidizers). Do not use solvent to thin. Respiratory protection is required when

ventilation is inadequate. NIOSH/OSHA approved respirators should be provided and worn.

Storage Requirements: Store in cool/dry location. Do not allow material to freeze, as product may be damaged. Store away from sparks and open flames.

08: EXPOSURE CONTROLS/PERSONAL PROTECTION

HMIS PP, H I Splash Goggles, Gloves, Apron, Vapor Respirator

VENTILATION: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs. Local exhaust ventilation is preferred because it

prevents containment dispersion into the work area controlling it as its source.

RESPIRATORY PROTECTION: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and if necessary, wear OSHA/NIOSH

approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne

contamination, and presence of sufficient oxygen.

PROTECTIVE CLOTHING/EQUIPMENT: Wear chemically protective gloves, boots and aprons to prevent prolonged or repeated skin contact. Wear protective goggles and face shield, per OSHA

eye and face protection (29 CFR 1910.133).

Separate contaminated work clothing from street clothing. Launder before reuse. Remove this material from your work shoes and clean personal protective CONTAMINATED EQUIPMENT:

equipment.

OTHER PRECAUTIONS: Never eat, drink or smoke in work areas.

This material is not listed by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

09: PHYSICAL & CHEMICAL PROPERTIES

Part A (Clear to light amber) Appearance:

Liquid

Physical State Boiling Point: ND

Odor: Part A (Mild)

Freezing/Melting Point: ND/NF ND

Insoluble Solubility: Vapor Pressure:

(Air = 1) > 1Vapor Density:

Spec Grav./Density: Part A (1.19)

VOC:

Part B (Amber)

Part B (.97)

Percent Volatile:

Part B (Amine odor) Flash Point:

Flash Point Method:

Burning Rate:

Autoignition Temp:

Evap Rate:

Viscosity:

No data available

No data available

0

>200° F

Slower than Butyl Acetate

Pensky Martens Closed Cup

Brookfield 500 cps (Part A) and 80 cps (Part B)

10: STABILITY AND REACTIVITY

Stable Stability: Conditions to Avoid: None

Strong oxidizers, acids and bases Materials to Avoid:

Hazardous Decomposition Products: CO, CO2, NOX Hazardous Polymerization:

11: TOXICOLOGICAL INFORMATION

Inhalation: Harmful if inhaled and may cause delayed lung injury. Can cause severe respiratory tract burns. Risk of serious damage to the lungs. May

cause nose, throat and lung irritation. Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory

system.

Skin Contact: Causes skin burns.

Eye Contact: Causes eye burns. May cause blindness. Severe eye irritation.

If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach. Ingestion: Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause: Sore throat, Eye disease, Skin Prolonged exposure

Disorders and Allergies.

This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater. Prolonged contact may result in chemical burns and permanent damage



1-888-684-3889 | www.RhinoCarbonFiber.com

SAFETY DATA SHEET

RCF™ Structural Epoxy Injection Resin | Revision Date 7/25/2019

1633 Thornwood Dr. Heath, OH 43056 USA P: +1 888 684 3889 E: info@rhinocarbonfiber.com

03

12: ECOLOGICAL INFORMATION

Aquatic toxicity Very toxic to aquatic organisms, may cause long term adverse effects in the

Toxicity to other organisms: No data available

13: DISPOSAL CONSIDERATIONS

When disposed of properly, this material does not meet RCRA classification or listing for hazardous waste. Never dispose of liquid to a landfill. Spilled material should be stabilized of solified prior to disposal. Once stabilized/solidified, the material may be disposed of through normal means. Certain localities and state laws have specific disposal requirements for non-hazardous industrial chemicals. Consult local municipal authorities, landfull personnel or disposal companies for details prior to any disposal activity. Always follow local, state and federal regulations.

14: TRANSPORT INFORMATION

Part A: Not hazardous for domestic ground shipment

Part A IMDG: UN 3082 Environmentally hazardous substance, liquid, n.o.s. (epoxy resin) 9 III MARINE POLLUTANT

Part B: UN 1760 Corrosive liquids, n.o.s. (nonylphenol) 8 III (ERG #154)
Part B IMDG: UN 1760 Corrosive liquids, n.o.s (nonylphenol) 8 III MARINE POLLUTANT
Segregation Group: 18 Alkalis
Placards required over 1,000 lbs.

15: REGULATORY INFORMATION

This product is a "Hazardous Chemical" as defined by the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories Immediate Hazard Yes
Delayed Hazard Yes
Fire Hazard No
Pressure Hazard No
Reactivity Hazard No
Section 302 Extremely hazardous substance No
Section 311 Extremely hazardous chemical Yes

State Regulations This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

16: OTHER INFORMATION

Rating Scale: 0-4

HMIS II ratings: Health = 3, Fire = 1, Reactivity = 2 HMIS III ratings: Health = 3, Fire = 1, Physical Hazard = 2 NFPA ratings: Health = 3, Fire = 1, Reactivity = 2

The information and recommendation in this document are based on the best information available to us at the time of preparation. We make no other warranty, expressed or implied, as to its correctness or completeness, or as to the results or reliance of this product.

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

User Responsibility: The information in this document cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions, in addition to those described herein, are required. Any health hazard and safety information herein should be distributed to customers or employees as applicable.

17: DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate and current as of the date of this SDS. However, since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representation or warranties, either expressed or implied, as to its correctness or completeness, or as of merchantability, fitness for a particular purpose, or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers or as to the results or reliance of this product. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

END OF SDS DOCUMENT



1-888-684-3889 | www.RhinoCarbonFiber.com